

Cross Country Mfg., Inc.
Specification Sheet

“Rancher” Series Trailers

STANDARD FEATURES

Model 4T16 – Four Ton Capacity Equipment Trailer

Electric brakes on both axles, smooth steel fenders, stake pockets for tie down, 5” channel tongue, 2000# tongue jack, 2” x 8” pressure treated deck, fixed 2 5/16” ball coupler, re-charging break-away kit, bias ply tires, vertical travel 54” ladder ramps, rubber mounted lights with sealed wiring harness, tandem 5200# axles with double eye spring suspension.

Model 616ECH – Three Ton Capacity Equipment/Car Hauler Trailer

Electric brakes on both axles, stake pockets for tie down, 2000# tongue jack, 2” x 8” pressure treated deck, fixed 2 5/16” ball coupler, re-charging break-away kit, bias ply tires, ramps store on sides of trailer, D.O.T. approved lighting.

Model CC510 – Single Axle Utility Trailer

Straight tube Tongue, 13” bias ply tires, vertical travel 4’ landscape ramp, 2” ball coupler, treated plank deck, landscape rail on 3 sides, D.O.T. approved lighting.

Model 610DTL – Deck Over the Wheels Dump Trailer

Tandem 5200# axles, ST225/75D15D tires on 6 bolt white spoke. 12 gauge floor with 14 gauge sides, 20” sides. Four full height stake pockets, Single 3” ram, 2 5/16” ball coupler, tongue jack with foot, safety chains, double acting rear tailgate, DOT approved lights, power up and power down, mud flaps.

Model 610DTLP – Low profile Dump Trailer

Tandem 5200# axles, ST225/75D15D tires on 6 bolt white spoke, 12 gauge floor with 14 gauge sides, 20” sides. Four full height stake pockets, single 3” ram, 2 5/16” ball coupler. Tongue jack with foot, safety chains, double acting rear tailgate, DOT approved lights, power up and power down, mud flats, smooth steel fenders.

SPECIFICATIONS

	<u>4T16</u>	<u>616ECH</u>	<u>CC510</u>	<u>610DTL</u>	<u>610DTLP</u>
G.V.W.R.	9996 lbs.	8050 lbs.	2990 lbs.	9996 lbs.	9996 lbs.
Capacity	8036 lbs.	5990 lbs.	2245 lbs.	8196 lbs.	7516 lbs.
Bed Size	82" W x 16' L	78" W x 16' L	63" W x 10' L	72" W x 10' L	72" W x 10' L
Tire Size	ST225/75D15D	ST205/75D14C	ST175/80D13C	ST225/75D15D	ST225/75D15D

AVAILABLE OPTIONS

Call Your Local Dealer for Available Options

Specifications subject to change without notice